

# Technical Data Displayglass

## Type AR 3000 / 90 G80 SP



### *Detailed Information*

<b>Technical Construction</b>	<ul style="list-style-type: none"><li>- AR 3000 / 90 G80, 2 mm (<math>\pm 0,2</math>)</li><li>- PVB-foil 0,38 mm</li><li>- displayglass, 2 mm (<math>\pm 0,2</math>) (total thickness: 4,38 mm)</li></ul>
<b>Anti-Reflection</b>	chemical – front side, gloss value 80
<b>Transmission</b>	approx. 90 %
<b>Dimensions</b>	production according to customer specifications tolerance*: $\pm 1$ mm
<b>Glass Thickness</b>	approx. 2,6 mm / 4,38 mm / 5,38 mm / 6,38 mm
<b>Finishing*</b>	seamed edges, dubbed corners, CNC edge finishing available. In order to protect the glasses from scratches, they are packed individually in special tissue paper.
<b>Delivery Time</b>	on stock
<b>Application</b>	front glass for LCD monitors
<b>Possible Combinations</b>	<ul style="list-style-type: none"><li>- available as anti-reflective EMC-shielding glass</li><li>- available as anti-reflective heating glass</li><li>- screen print</li></ul>

Please contact us if you want to have displayglass mounted in your front panels or frames.

\* standard